

#### MATERIAL DATA SAFETY SHEET

Issued in Australia by Bilby 3D Pty Ltd.

The attached Material Data Safety Sheet has been prepared by the manufacturer outside Australia.

In accordance with Australia WHS regulations the following Australian contact details apply

## Section 1: AUSTRALIAN COMPANY DETAILS

In Australia the product is imported and distributed by: Bilby 3D Pty Ltd Mailing Address : Kingsgrove Business Centre, 7/192 Kingsgrove Rd, Kingsgrove NSW 2208 Head Office Address : Kingsgrove Business Centre, 7/192 Kingsgrove Rd, Kingsgrove NSW 2208 Contact Phone: 1800 847 333

## Section 2: AUSTRALIAN EMERGENCY CONTACT

#### **Emergency Contact**

In the event of an emergency please contact: Poisons Information Centre 24 hour Telephone Advice Line on 13 11 26

## Section 3: AUSTRALIAN ISSUE DATA

Date of Issue : 1 March 2020



🗆 • BASF

We create chemistry

# Ultracur3D<sup>®</sup> RG 1100

Rigid resin with superior stiffness and temperature resistance

## Technical Data Sheet

General Properties	Norm	Typical Values
Appearance	-	Clear
Viscosity, 30 °C	Cone/Plate Rheometer <sup>1</sup>	201 mPas
Viscosity, 50 °C	Cone/Plate Rheometer <sup>1</sup>	65 mPas
Density (printed part)	ASTM D792	1.2 g/cm <sup>3</sup>
Density (liquid resin)	ASTM D4052-18a	1.12 g/cm <sup>3</sup>

Tensile Properties	Norm (5 mm/min)	Typical Values
E Modulus	ASTM D638	3080 MPa
Ultimate Tensile Strength	ASTM D638	70 MPa
Elongation at Break	ASTM D638	5 %

Flexural Properties	Norm	Typical Values
Flexural Modulus	ASTM D790	2880 MPa
Flexural Strength	ASTM D790	119 MPa

Impact Properties	Norm	Typical Values
Notched Izod (Machined), 23 °C	ASTM D256	16 J/m
Charpy notched, 23 °C	ISO 179-1	0.6 kJ/m <sup>2</sup>

Thermal Properties	Norm	Typical Values
HDT at 0.45 MPa	ASTM D648	116 °C
HDT at 1.82 MPa	ASTM D648	84 °C
Flammability	UL 94 1.5 mm	HB

Hardness	Norm	Typical Values
Shore D	ASTM D2240	85

Other	Norm	
Water Absorption, Short Term	ASTM D570	0.32 %
(24 hours)		

1) Determined with TA-Instrument DHR rheometer, cone/plate, diameter 60 mm, shear rate 100 s<sup>-1</sup>

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed. The safety data given in this publication is for information purposes only and does not constitute a legally binding MSDS. The relevant MSDS can be obtained upon request from your supplier or you may contact BASF 3D Printing Solutions GmbH directly at sales@basf-3dps.com. Version 2.1

BASF 3D Printing Solutions GmbH

sales@basf-3dps.com

www.forward-am.com